

किंग जार्ज चिकित्सा विश्वविद्यालय उ०प्र०, लखनऊ— 226003 निर्माण विभाग

फोन (कुलसचिव कार्यालय) : 0522-2253171 Email eng.civil@kgmcindia.edu

पत्रांकः 1637/M-10/2023

दिनांक 38/11/23

QUOTATION NOTICE

To,	
	M/s

Details of work as given below:-

Dismantling doors, windows and clerestory windows (steel or wood) shutter including chowkhats. architrave, holdfasts etc. complete and stacking within 50 metres lead. 2	S.NO	Particulars	Quantity	Unit	Rate	
P/F of Descon make or equivalent Solid PVC door frames of 65mm x 46mm & shutter 25mm (Solid thick with ribs) Grey/Dark Grey/Black thick mode of Foam PVC sheet including Aluminium hardware, sliding bolt, Handles & hinges. 3 Providing and fixing white vitreous china pedestal type water closet (European type w.o. pan) including all fixtures, cost of material, labour T&P complete in all respect. 5 P/F wash basin of size 630x450mm with C.I brackets,15mm C.P brass pillar taps,32mm C.P brass waste of standard pattern,including painting of fittings and brackets,cutting and making good the walls wherever require. 6 S/F 10 Lit PVC low down cistern for appd, quality in completed. 7 P/F brass bib cock 15mm dia, of approved quality. 8 Providing and fixing 8mm dia C.P/S.S Jet with flexible tube 1 meter long with S.S tringular plate to European type W.C of quality and make as approved by Engineer-in-charge. 9 P/F Chlorinated polyvinyl chloride (CPVC) pipes 20mm dia,having thermal stability for hot and cold water supply,including all cype plain and brass threaded fittings, including fixing the pipe with clamps at Im spacing. This includes jointing of pipes and fittings with one step CPVC solvent cement and testing of joints complete as per direction of Engineer-in-charge. Internal work. 10 P/F PVC Pipe 75mm dia 6kg pressure ISI make. 11 P/F PVC Pipe 75mm dia 6kg pressure ISI make. 12 Providing and fixing double scaffolding system (cup lock type) on the exterior side, up to seven story height made with 40 mm dia M.S. tube 1.5 m centre to centre, horizontal & vertical tubes joining with cup & lock system with M.S. tubes. M.S. tube challies. M.S. clamps and M.S. staircase system in the scaffolding for working platform etc. and maintaining it in a serviceable condition for the required duration as approved and removing it there after. The scaffolding system shall be stiffened with bracings, runners, connection with the building etc wherever required for inspection of work at required locations with essential safety featur		stacking within 50 metres lead.	7.10			
thick mode of Foam PVC sheet including Aluminium hardware, sliding bolt, Handles & hinges. 3 Providing and fixing M.C.P sheet. 4 Providing and fixing white vitreous china pedestal type water closet (European type w.o. pan) including all fixtures, cost of material, labour T&P complete in all respect. 5 P/F wash basin of size 630x450mm with C.I brackets, I5mm C.P brass pillar taps, 32mm C.P brass waste of standard pattern, including painting of fittings and brackets, cutting and making good the walls wherever require. 6 S/F 10 Lit PVC low down eistern for appd, quality in completed. 7 P/F brass bib cock 15mm dia. of approved quality. 8 Providing and fixing 8mm dia C.P/S.S Jet with flexible tube I meter long with S.S tringular plate to European type W.C of quality and make as approved by Engineer-in-charge. 9 P/F Chlorinated polyvinyl chloride (CPVC) pipes 20mm dia.having thermal stability for hot and cold water supply, including all cynce plain and brass threaded fittings, including fixing the pipe with clamps at 1m spacing. This includes jointing of pipes and fittings with one step CPVC solvent cement and testing of joints complete as per direction of Engineer-in-charge. Internal work. 10 P/F PVC Pipe 15mm dia 6kg pressure ISI make. 11 P/F PVC Pipe 100mm dia 6kg pressure ISI make. 12 Providing and fixing double scaffolding system (cup lock type) on the exterior side, up to seven story height made with 40 mm dia M.S. tube 1.5 m centre to centre, horizontal & vertical tubes joining with cup & lock system with M.S. tubes, M.S. tube challies, M.S. clamps and M.S. staircase system in the scaffolding for working platform etc. and maintaining it in a serviceable condition for the required duration as approved and removing it there after. The scaffolding system shall be stiffened with bracings, runners, connection with the building etc wherever required for inspection of work at required locations with essential safety features for the workmen etc. complete as per directions and approved of Engineer-in-charge.	2	P/F of Descon make or equivalent Solid PVC door frames of 65mm		No.		
Providing and fixing A.C.P sheet. Providing and fixing white vitrous china pedestal type water closet (European type w.o. pan) including all fixtures, cost of material, labour T&P complete in all respect. P/F wash basin of size 630x450mm with C.I brackets, I5mm C.P brass pillar taps, 32mm C.P brass waste of standard pattern, including painting of fittings and brackets, cutting and making good the walls wherever require. S/F 10 Lit PVC low down cistern for appd, quality in completed. P/F brass bib cock I5mm dia. of approved quality. Providing and fixing 8mm dia C.P/S.S Jet with flexible tube I meter long with S.S tringular plate to European type W.C of quality and make as approved by Engineer-in-charge. P/F Chlorinated polyvinyl chloride (CPVC) pipes 20mm dia.having thermal stability for hot and cold water supply, including all cpvc plain and brass threaded fittings, including fixing the pipe with clamps at Im spacing. This includes jointing of pipes and fittings with one step CPVC solvent cement and testing of joints complete as per direction of Engineer-in-charge. Internal work. P/F PVC Pipe 75mm dia 6kg pressure ISI make. Providing and fixing double scaffolding system (cup lock type) on the exterior side, up to seven story height made with 40 mm dia M.S. tube 1.5 m centre to centre. horizontal & vertical tubes joining with cup & lock system with M.S. tubes. M.S. tube challies. M.S. clamps and M.S. staircase system in the scaffolding for working platform etc. and maintaining it in a serviceable condition for the required duration as approved and removing it there after. The scaffolding system shall be stiffened with bracings. runners, connection with the building etc wherever required for inspection of work at required locations with essential safety features for the workmen etc. complete as per directions and approval of Engineer-in-charge.		thick mode of Foam PVC sheet including Aluminium hardware sliding	x= ti = a			
Providing and fixing white vitreous china pedestal type water closet (European type w.o. pan) including all fixtures, cost of material, labour T&P complete in all respect. 5		Providing and fixing A.C.P sheet	0 -:			
T&P complete in all respect. D/F wash basin of size 630x450mm with C.I brackets,15mm C.P brass pillar taps,32mm C.P brass waste of standard pattern.including painting of fittings and brackets,cutting and making good the walls wherever require. O1	4	Providing and fixing white vitreous china nedestal type water along	0.51	Sqm.		
5 P/F wash basin of size 630x450mm with C.I brackets,15mm C.P brass pillar taps,32mm C.P brass waste of standard pattern.including painting of fittings and brackets.cutting and making good the walls wherever require. 6 S/F 10 Lit PVC low down cistern for appd. quality in completed. 7 P/F brass bib cock 15mm dia. of approved quality. 8 Providing and fixing 8mm dia C.P/S.S Jet with flexible tube 1 meter long with S.S tringular plate to European type W.C of quality and make as approved by Engineer-in-charge. 9 P/F Chlorinated polyvinyl chloride (CPVC) pipes 20mm dia.having thermal stability for hot and cold water supply.including all cpvc plain and brass threaded fittings, including fixing the pipe with clamps at 1m spacing.This includes jointing of pipes and fittings with one step CPVC solvent cement and testing of pipes and fittings with one step CPVC solvent cement and testing of pipes and fittings with one step CPVC solvent cement and testing of pipes and fittings with one step CPVC solvent cement and testing of pipes and fittings with one step CPVC solvent cement and testing of pipes and fittings with one step CPVC solvent cement and testing of pipes and fittings with one step CPVC solvent cement and testing of pipes and fittings with one step CPVC solvent cement and testing of pipes and fittings with one step CPVC solvent cement and testing of pipes and fittings with one step CPVC solvent cement and testing of pipes and fittings with one step CPVC solvent cement and testing of pipes and fittings with one step CPVC solvent cement and testing of pipes and fittings with one step CPVC solvent cement and testing of pipes and fittings with one step CPVC solvent cement and testing of pipes and fittings with one step CPVC solvent cement and testing of pipes and fittings with one step CPVC solvent cement and testing of pipes cement solvent cement and testing of pipes cement solvent cement solvent cement and testing of pipes cement solvent cement solvent cement solvent cement solvent cement solvent solvent solvent		T&P complete in all respect.				
7 P/F brass bib cock 15mm dia. of approved quality. 8 Providing and fixing 8mm dia C.P/S.S Jet with flexible tube 1 meter long with S.S tringular plate to European type W.C of quality and make as approved by Engineer-in-charge. 9 P/F Chlorinated polyvinyl chloride (CPVC) pipes 20mm dia.having thermal stability for hot and cold water supply, including all cpvc plain and brass threaded fittings, including fixing the pipe with clamps at 1m spacing. This includes jointing of pipes and fittings with one step CPVC solvent cement and testing of joints complete as per direction of Engineer-in-charge. Internal work. 10 P/F PVC Pipe 75mm dia 6kg pressure ISI make. 11 P/F PVC Pipe 100mm dia 6kg pressure ISI make. 12 Providing and fixing double scaffolding system (cup lock type) on the exterior side, up to seven story height made with 40 mm dia M.S. tube 1.5 m centre to centre, horizontal & vertical tubes joining with cup & lock system with M.S. tubes, M.S. tube challies, M.S. clamps and M.S. staircase system in the scaffolding for working platform etc. and maintaining it in a serviceable condition for the required duration as approved and removing it there after. The scaffolding system shall be stiffened with bracings, runners, connection with the building etc wherever required for inspection of work at required locations with essential safety features for the workmen etc. complete as per directions and approval of Engineer-in-charge. 13 Repair of old aluminium door/windows. 5,27 Sqm. 14 Providing Plumber with helper for removing and refixing of old fittings. 01 No.	5	P/F wash basin of size 630x450mm with C.I brackets,15mm C.P brass pillar taps,32mm C.P brass waste of standard pattern including pointing of		No.	# # # # # # # # # # # # # # # # # # #	
7 P/F brass bib cock 15mm dia. of approved quality. 8 Providing and fixing 8mm dia C.P/S.S Jet with flexible tube 1 meter long with S.S tringular plate to European type W.C of quality and make as approved by Engineer-in-charge. 9 P/F Chlorinated polyvinyl chloride (CPVC) pipes 20mm dia.having thermal stability for hot and cold water supply.including all cpvc plain and brass threaded fittings, including fixing the pipe with clamps at 1m spacing. This includes jointing of pipes and fittings with one step CPVC solvent cement and testing of joints complete as per direction of Engineer-in-charge. Internal work. 10 P/F PVC Pipe 15mm dia 6kg pressure ISI make. 6.00 Rmt. 11 P/F PVC Pipe 100mm dia 6kg pressure ISI make. 6.00 Rmt. 12 Providing and fixing double scaffolding system (cup lock type) on the exterior side, up to seven story height made with 40 mm dia M.S. tube 1.5 m centre to centre, horizontal & vertical tubes joining with cup & lock system with M.S. tubes. M.S. tube challies. M.S. clamps and M.S. staircase system in the scaffolding for working platform etc. and maintaining it in a serviceable condition for the required duration as approved and removing it there after. The scaffolding system shall be stiffened with bracings, runners, connection with the building etc wherever required for inspection of work at required locations with essential safety features for the workmen etc. complete as per directions and approval of Engineer-in-charge. 13 Repair of old aluminium door/windows. 14 Providing Plumber with helper for removing and refixing of old fittings. 15 Providing Plumber with helper for removing and refixing of old fittings. 16 No.	6	S/F 10 Lit PVC low down distant for and and it		No.		
Providing and fixing 8mm dia C.P/S.S Jet with flexible tube 1 meter long with S.S tringular plate to European type W.C of quality and make as approved by Engineer-in-charge. P/F Chlorinated polyvinyl chloride (CPVC) pipes 20mm dia.having thermal stability for hot and cold water supply.including all cpvc plain and brass threaded fittings. including fixing the pipe with clamps at 1m spacing.This includes jointing of pipes and fittings with one step CPVC solvent cement and testing of joints complete as per direction of Engineer-in-charge. Internal work. P/F PVC Pipe 75mm dia 6kg pressure ISI make. Providing and fixing double scaffolding system (cup lock type) on the exterior side, up to seven story height made with 40 mm dia M.S. tube 1.5 m centre to centre, horizontal & vertical tubes joining with cup & lock system with M.S. tubes. M.S. tube challies. M.S clamps and M.S. staircase system in the scaffolding for working platform etc. and maintaining it in a serviceable condition for the required duration as approved and removing it there after. The scaffolding system shall be stiffened with bracings, runners, connection with the building etc wherever required for inspection of work at required locations with essential safety features for the workmen etc. complete as per directions and approval of Engineer-in-charge. Repair of old aluminium door/windows. Rmt. 12.00 Sqm. 12.00 Sqm.	-	P/F brass bib cock 15mm die of approved avalle		No.		
with S.S tringular plate to European type W.C of quality and make as approved by Engineer-in-charge. 9		Providing and fiving 2mm die C. D.C. C. L 11 G	. 01	No.		
P/F Chlorinated polyvinyl chloride (CPVC) pipes 20mm dia.having thermal stability for hot and cold water supply,including all cpvc plain and brass threaded fittings. including fixing the pipe with clamps at 1m spacing. This includes jointing of pipes and fittings with one step CPVC solvent cement and testing of joints complete as per direction of Engineer-in-charge. Internal work. 10		With S.S tringular plate to European type W.C. of quality and make as	0.1			
and brass threaded fittings, including fixing the pipe with clamps at Im spacing. This includes jointing of pipes and fittings with one step CPVC solvent cement and testing of joints complete as per direction of Engineer-in-charge. Internal work. 10 P/F PVC Pipe 75mm dia 6kg pressure ISI make. 11 P/F PVC Pipe 100mm dia 6kg pressure ISI make. 12 Providing and fixing double scaffolding system (cup lock type) on the exterior side, up to seven story height made with 40 mm dia M.S. tube 1.5 m centre to centre, horizontal & vertical tubes joining with cup & lock system with M.S. tubes, M.S. tube challies, M.S. clamps and M.S. staircase system in the scaffolding for working platform etc. and maintaining it in a serviceable condition for the required duration as approved and removing it there after. The scaffolding system shall be stiffened with bracings, runners, connection with the building etc wherever required for inspection of work at required locations with essential safety features for the workmen etc. complete as per directions and approval of Engineer-in-charge. 13 Repair of old aluminium door/windows. 14 Providing Plumber with helper for removing and refixing of old fittings. 15 Providing lubour for elevitive for inspection of with clamps at Improved and removing in the providing and refixing of old fittings.	9	P/F Chlorinated polyvinyl chloride (CPVC) pines 20mm die havin	01	No.	-	
P/F PVC Pipe 100mm dia 6kg pressure 1SI make. 12 Providing and fixing double scaffolding system (cup lock type) on the exterior side, up to seven story height made with 40 mm dia M.S. tube 1.5 m centre to centre, horizontal & vertical tubes joining with cup & lock system with M.S. tubes, M.S. tube challies, M.S clamps and M.S. staircase system in the scaffolding for working platform etc. and maintaining it in a serviceable condition for the required duration as approved and removing it there after. The scaffolding system shall be stiffened with bracings, runners, connection with the building etc wherever required for inspection of work at required locations with essential safety features for the workmen etc. complete as per directions and approval of Engineer-in-charge. 13 Repair of old aluminium door/windows. 14 Providing Plumber with helper for removing and refixing of old fittings. 5.27 Sqm. Providing Islands for the providing plants for the providing of old fittings.		and brass threaded fittings, including fixing the pipe with clamps at Im spacing. This includes jointing of pipes and fittings with one step CPVC solvent cement and testing of joints complete as per direction of Engineer-in-charge. Internal work.	12.00	Rmt.		
Providing and fixing double scaffolding system (cup lock type) on the exterior side, up to seven story height made with 40 mm dia M.S. tube 1.5 m centre to centre, horizontal & vertical tubes joining with cup & lock system with M.S. tubes, M.S. tube challies, M.S clamps and M.S. staircase system in the scaffolding for working platform etc. and maintaining it in a serviceable condition for the required duration as approved and removing it there after. The scaffolding system shall be stiffened with bracings, runners, connection with the building etc wherever required for inspection of work at required locations with essential safety features for the workmen etc. complete as per directions and approval of Engineer-in-charge. 13 Repair of old aluminium door/windows. 14 Providing Plumber with helper for removing and refixing of old fittings. 15 Providing Islander for the scaffolding system shall be stiffened with bracings, runners, connection with the building etc wherever required for inspection of work at required locations with essential safety features for the workmen etc. complete as per directions and approval of Engineer-in-charge. 18 Repair of old aluminium door/windows. 19 Providing Plumber with helper for removing and refixing of old fittings. 19 Providing Plumber for elements of its state of the providing state of the prov		P/F PVC Pipe 75mm dia 6kg pressure ISI make.	6.00	Rimt		
Providing and fixing double scaffolding system (cup lock type) on the exterior side, up to seven story height made with 40 mm dia M.S. tube 1.5 m centre to centre, horizontal & vertical tubes joining with cup & lock system with M.S. tubes, M.S. tube challies, M.S. clamps and M.S. staircase system in the scaffolding for working platform etc. and maintaining it in a serviceable condition for the required duration as approved and removing it there after. The scaffolding system shall be stiffened with bracings, runners, connection with the building etc wherever required for inspection of work at required locations with essential safety features for the workmen etc. complete as per directions and approval of Engineer-in-charge. 13 Repair of old aluminium door/windows. 14 Providing Plumber with helper for removing and refixing of old fittings. 15 Providing Islands for the scaffolding system (cup lock type) on the exterior side, up to M.S. tube 1.5 m centre (cup lock type) on the exterior side, up to M.S. tube 1.5 m centre (cup lock type) on the exterior side, up to M.S. tube 1.5 m centre (cup lock type) on the exterior side, up to M.S. tubes (cup lock type) on the exterior side (P/F PVC Pipe 100mm dia 6kg pressure ISI make.	THE RESIDENCE OF THE PARTY OF T	The second secon		
staircase system in the scaffolding for working platform etc. and maintaining it in a serviceable condition for the required duration as approved and removing it there after. The scaffolding system shall be stiffened with bracings, runners, connection with the building etc wherever required for inspection of work at required locations with essential safety features for the workmen etc. complete as per directions and approval of Engineer-in-charge. 13 Repair of old aluminium door/windows. 14 Providing Plumber with helper for removing and refixing of old fittings. 15 Providing lobour for elemination of the required duration as approved and removing and required duration as approved and removing with the building etc. 14 Providing Plumber with helper for removing and refixing of old fittings. 15 Providing below for elemination of the required duration as approved and removing at required duration as approved and removing the required duration as approved the required duration as approved the required duration as approved to the required duration as appro	12	Providing and fixing double scaffolding system (cup lock type) on the exterior side, up to seven story height made with 40 mm dia M.S. tube 1.5 m centre to centre, horizontal & vertical tubes joining with cup & lock system with M.S. tubes, M.S. tube challies, M.S. clamps and M.S.		King.		
wherever required for inspection of work at required locations with essential safety features for the workmen etc. complete as per directions and approval of Engineer-in-charge. 13 Repair of old aluminium door/windows. 14 Providing Plumber with helper for removing and refixing of old fittings. 15 Providing labour for eleminating of the providing labour for elementary elementa	u.	staircase system in the scaffolding for working platform etc. and maintaining it in a serviceable condition for the required duration as approved and removing it there after. The scaffolding system shall be				
13 Repair of old aluminium door/windows. 14 Providing Plumber with helper for removing and refixing of old fittings. 15 Providing labour for eleminating of the plant of the		wherever required for inspection of work at required locations with essential safety features for the workmen etc. complete as per directions and approval of Engineer-in-charge.	12.00	Sqm.		
14 Providing Plumber with helper for removing and refixing of old fittings. 01 No.		Repair of old aluminium door/windows.	5 27	Sam		
15 Providing labour for algoring of site and the site		Providing Plumber with helper for removing and refixing of old fittings	CONTRACTOR OF THE PERSON NAMED IN COLUMN TWO IS NOT THE OWNER.			
	15	Providing labour for cleaning of site and collecting malwa	COLUMN TO THE PARTY OF THE PART			

Terms & Conditions

1.G.S.T and labour cess shall be paid or deducted as per rules applicable.





किंग जार्ज चिकित्सा विश्वविद्यालय उ०प्र०, लखनऊ— 226003 निर्माण विभाग

फोन (कुलसचिव कार्यालय) : 0522-2257540 Email eng.civil@kgmcindia.edu

			7.0022-22	37340	email eng.civi
पत्रांक	ō·				W-000000000000000000000000000000000000
1 -11 92					

दिनांक:

1.G.S.T and labour cess shall be paid or deducted as per rules applicable. 2. The work will be completed within given time.

3. Quantity can be increase or decrease as per requirements.

4. Conditional quotations are liable to be rejected.

5. The undersigned reserves the right to reject quotations in part or whole without assigning any reason.

Yours faithfully

(Shailendra singh) Executive Engineer

umar Raj) Superintending Engineer

Def No-1637 M+0/2013

Copy for information and necessary action to:-

1.Registrar, King George's Medical University U.P, Lucknow.

4. Sri Anjani kumar, Assistant Engineer, Works deptt. K.G.M.U.U.P.Lucknow

5. Sri Prateek Dubey, Junior Engineer, Works deptt. K.G.M.U.U.P.Lucknow

Yours faithfully

(Shailendfa singh) **Executive Engineer**

(Dinesh Kumar Raj) Superintending Engineer